



A Heytex group company

STYLE: C14656
TufMesh Plus
Vinyl Coated Polyester
Flame Retardant Woven Mesh

TYPICAL PERFORMANCE PROPERTIES

Total Weight

ASTM D-751 14 oz. / yd.²

Base Fabric Construction

17 x 11, 1000 Denier

Shade Factor

65%

Grab Tensile

ASTM D-751 390 x 290 lbs.

Strip Tensile

ASTM D-751 290 x 210 lbs. / in.
Procedure B

Tongue Tear

ASTM D-751 40 x 45 lbs.
8x10 Specimen @ 12 in. / min.

Trap Tear

ASTM D-751 45 x 40 lbs.

Low Temperature

- 40° F

ASTM D-2136

UV Resistance

ASTM G-53 1200 Hours

Flame Resistance

Cal. Fire Marshal-Title 19 Pass
NFPA 701 Pass

Date Issued: September 6, 2010

We believe this information is the best currently available, but assume no obligation or liability in connection therewith. We make no guarantee of results and no representation that the material is fit for any particular purpose. There are NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY, unless specified in writing and signed by BondCote Corporation

P: 540.980.4461 | 800.255.9338 | F: 540.980.4466
P.O. Box 729, 509 Burgis Avenue, Pulaski, VA 24301
www.bondcote.com ISO 9001: 2008 Certified