



A Heytex group company

STYLE: G604849020720A
Vinyl Coated Polyester
Irrigation Material

TYPICAL PERFORMANCE PROPERTIES

Total Weight

ASTM D-751 6 oz. / yd.²

Grab Tensile

ASTM D-751 175 x 160lbs.

Strip Tensile

ASTM D-751 140 x 120 lbs. / in.
Procedure B

Tongue Tear

ASTM D-751 25 x 25 lbs.
8x10 Specimen @ 12 in. / min.

Adhesion

ASTM D-751 7 lbs. / in.

Hydrostatic Resistance

ASTM D-751 90 psi
Procedure A

Low Temperature

ASTM D-2136 - 65 ° F

Date Issued: July 5, 2011

We believe this information is the best currently available, but assume no obligation or liability in connection therewith. We make no guarantee of results and no representation that the material is fit for any particular purpose. There are NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY, unless specified in writing and signed by BondCote Corporation

P: 540.980.4461 | 800.255.9338 | F: 540.980.4466
P.O. Box 729, 509 Burgis Avenue, Pulaski, VA 24301
www.bondcote.com ISO 9001: 2008 Certified